



## Medium / High Pressure DIAMOND - High Abrasion



Four spiral steel Hydraulic Hose meets or exceeds SAE 100 R16 and ISO 1307

VINCKE HH-04X

EN 856 4SH DIAMOND											
Code	Nominal $\varnothing$	Inside $\varnothing$	Braid $\varnothing$	Outside $\varnothing$	Max. Working Pressure	Burst Pressure	Minimum Bend Radius	Weight			
Dash Size	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m	
04X12	12	3/4"	19	28,2	32	420	6090	1680	24360	280	1465
04X16	16	1"	25,4	35,1	38,4	380	5510	1520	22040	340	2035
04X20	20	1 1/4"	31,8	41,9	45,2	350	5075	1400	20300	460	2385
04X24	24	1 1/2"	38,1	48,8	53	290	4205	1160	16820	560	3185
04X32	32	2"	50,8	63,2	67,6	250	3625	1000	14500	700	4365

### Construction:

**Tube:** seamless oil resistant synthetic rubber

**Reinforcement:** 3 high tensile steel wire braid

**Wrapped cover:** Super High abrasion and ozone, UV radiation, resistant synthetic rubber

**Temperature range:** -40°C + 100°C Max (max 120°C discontinuous)

