

# LOW PRESSURE



In Oil Return hose with steel wire helix. High Flexibility.

VINCKE HH-GR

GRECA-10										
Code	Nominal $\varnothing$	Inside $\varnothing$	Outside $\varnothing$	Max. Working Pressure		Burst Pressure		Minimum Bend Radius	Weight	
	Dash Size	inch	mm	mm	bar	psi	bar	psi	mm	g/m
GR-12	12	3/4"	19	29	10	145	30	435	35	494
GR-16	16	1"	25,4	35	10	145	30	435	50	601
GR-20	20	1 1/4"	32	42	10	145	30	435	60	814
GR-24	24	1 1/2"	38	48	10	145	30	435	85	948
GR-32	32	2"	50,8	63	10	145	30	435	120	1584
GR-40	40	2 1/2"	63,5	74	10	145	30	435	160	1786
GR-48	48	3"	76,2	90	10	145	30	435	200	2570
GR-64	64	4"	101,6	117,5	10	145	30	435	280	4234

**Construction:**

**Tube:** Oil and petrol resistant black NBR.

**Reinforcement:** High tensile synthetic textile, steel wire helix and antistatic copper wire.

**Wrapped cover:** Oil, weather, ozone, abrasion and sea water resistant, at-corrugated, special synthetic rubber.

**Fluid resistance:** For suction and discharge of petroleum products with aromatic content up to 50%

**Temperature range:** -30°C + 70°C Max

