



Low / Medium Pressure

One Compact Wire Braid Hydraulic Hose meets or exceeds EN 857 1 SC

VINCKE HH-17S

1SC SMOOTH											
Code	Nominal ø	Inside ø	Braid ø	Outside ø	Max. Working Pressure	Burst Pressure	Minimum Bend Radius	Weight			
Dash Size	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m	
1704S	04	1/4"	6,4	10,4	12,2	225	3263	1100	15950	50	180
1705S	05	5/16"	8	11,5	13,6	215	3118	1050	15225	55	200
1706S	06	3/8"	9,5	13,6	15,5	180	2610	880	12760	60	260
1708S	08	1/2"	12,7	17	19	160	2320	700	10150	70	345
1710S	10	5/8"	16	20,4	22,4	130	1885	650	9425	90	420
1712S	12	3/4"	19	23,8	25,8	105	1523	520	7540	100	495
1716S	16	1"	25,4	31,3	33,4	88	1276	430	6235	160	735

Construction:

Tube: seamless oil resistant synthetic rubber

Reinforcement: 1 high tensile steel wire braid

Smooth cover: weather, abrasion and ozone, resistant synthetic rubber

Fluid resistance: Hydraulic fluids on mineral, vegetable and synthetic oil, water based fluids.

Temperature range: -40°C + 100°C Max (max 120°C discontinuous)

